

DECOLED FLUX PLUS ROUND - DIMMABLE



* Classic shapes for immediate retro-fit of incandescent lamps in any decorative application: traditional chandeliers, abat-jours, fittings where the aesthetic of the lamp is important even when the lamp is off.

* Working from mains.

* Opal finish of the lamp cover, perfect replacement of opal incandescent lamps, no more available on the European market.

* Warm white light, suitable to a cozy environment.

* Extremely low energy consumption.

* Ceramic housing for the electronic components: better heat dissipation and more safety for the user.

* 110-132V version available upon request.

Item Characteristics

Code	CP4540WD
Lamp Voltage	200-240 V
Nominal Power	5 W
Base	E14
Lamp Current	0,04 A
Nominal Flux	400 LUMEN
Light Tonality	Warm White
Colour temperature	2700 K
Opening beam	200°
Diameter	45 mm
Length	72 mm

Performance

Irc/Ra	80
Lifetime	>25000 h
Energy Class	A+
kWh/1000h	5
Equivalence with incandescent lamp	36 W

Tech Info

Dimmable	YES
Operating Position	360°
Open fittings	YES
Number of ON-OFF cycles	100000
Power Factor	0,50
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3 -2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 244/2009 * Progettazione Eco Compatibile 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Shipping info

Single pack dimensions L x H x D (mm)	52 x 85 x 52
Item barcode	8011905839314
Pack	10 pz
Master barcode	8011905784591