

T26 - 220-240V



- * Classic shapes for immediate retro-fit of incandescent lamps in specific applications: traditional chandeliers, abat-jours, small fittings.
- * Opal finish of the lamp cover, perfect replacement of opal incandescent lamps, no more available on the European market.
- * Warm white light, suitable to a cozy environment.
- * Extremely low energy consumption.
- * Suitable also inside refrigerators

Item Characteristics

Code	L0121
Lamp Voltage	220-240 V
Nominal Power	2 W
Base	E14
Nominal Flux	115 LUMEN
Light Tonality	Warm White
Colour temperature	2700 K
Diameter	26 mm
Length	57 mm

Performance

Irc/Ra	>80
Lifetime	15000 h
Energy Class	A+
kWh/1000h	2
Equivalence with incandescent lamp	12 W

Tech Info

Dimmable	NO
Open fittings	YES
Number of ON-OFF cycles	100000
Power Factor	0,27
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3 -2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 244/2009 * Progettazione Eco Compatibile 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.

Shipping info

Single pack dimensions L x H x D (mm)	65 x 30 x 30
Item barcode	8011905836542
Pack	10 pz
Inner pack dimensions L x H x D (mm)	165 x 75 x 75
Master barcode	8011905781828
Master pack dimensions L x H x D (mm)	400 x 180 x 190