

TECNO VINTAGE GLOBE



* LED technology combined with remote phosphor technology have made it possible to engineer a product composed of a series of micro-led sources that optimise thermal management, they are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

* Pleasant warm colour and the 'filament effect', identical to traditional incandescent lamps.

* Excellent colour rendering.

* Excellent colour maintenance.

* Classic bulb shape: immediate retrofit of incandescent lamps in the same fittings: about-jour and fittings where the 'look' of the lamp is important also when the lights are off!

* Extremely low energy consumption

Item Characteristics

Code	LF0437W
Lamp Voltage	220-240 V
Nominal Power	6 W
Base	E27
Lamp Current	0,052 A
Nominal Flux	660 LUMEN
Light Tonality	Warm white
Colour temperature	2700 K
Opening beam	360°
Diameter	125 mm
Lenght	175 mm

Performance

Irc/Ra	>80
Lifetime	15000 h
Energy Class	A++
kWh/1000h	6
Equivalence with incandescent lamp	52 W

Tech Info

Dimmable	NO
Operating Position	360°
Open fittings	YES
Number of ON-OFF cycles	100000
Power Factor	0,5
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C

Fulfilled Directives and norms

2011/65/UE * RoHS 2012/19/UE * RAEE
2014/30/UE * Compatibilità Elettromagnetica
2014/35/UE * Bassa Tensione EN 61547 *
anno 2010 EN 55015 * anno 2014 EN 61000-3
-2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3
* anno 2014 EN 62471 * anno 2010 IEC/TR
62471-2 EN 62031 * anno 2009 (+A1:2013)
EN 62560 * anno 2013 EN 60968 * anno 2013
244/2009 * Progettazione Eco Compatibile
2010/30/EU * Energy Consumption 874/2012 *
Regulation for Energy Labelling 2009/125/CE *
Progettazione Eco Compatibile 1194/2012 *
Progettazione Eco Compatibile

Shipping info

Item barcode	8011905841461
Pack	10 pz
Master barcode	8011905786748